

EWR PIPES

Size Range / Tubing

Size	Outside Diameter		Wall Thickness		Weight	
	in	mm	in	mm	lb/ft	kg/m
3/4	1.05	26.7	0.113	2.9	1.13	1.7
	1.05	26.7	0.154	3.9	1.48	2.19
1	1.315	33.4	0.133	3.4	1.68	2.52
	1.315	33.4	0.179	4.5	2.17	3.21
1 1/4	1.66	42.2	0.125	3.2	2.05	3.08
	1.66	42.2	0.14	3.6	2.27	3.43
	1.66	42.2	0.191	4.9	3	4.51
1 1/2	1.9	48.3	0.125	3.2	2.37	3.56
	1.9	48.3	0.145	3.7	2.72	4.07
	1.9	48.3	0.2	5.1	3.63	5.43
	1.9	48.3	0.25	6.4	4.41	6.6
	1.9	48.3	0.3	7.6	5.13	7.63
	1.9	48.3	0.3	7.6	5.13	7.63
2	2.375	60.3	0.167	4.2	3.94	5.81
	2.375	60.3	0.19	4.8	4.44	6.57
	2.375	60.3	0.254	6.5	5.76	8.62
	2.375	60.3	0.295	7.5	6.56	9.77
	2.375	60.3	0.336	8.5	7.32	10.86
2 1/2	2.875	73	0.217	5.5	6.17	9.16
	2.875	73	0.276	7	7.67	11.39
	2.875	73	0.308	7.8	8.45	12.54
	2.875	73	0.34	8.6	9.21	13.66
	2.875	73	0.392	10	10.4	15.54
	2.875	73	0.44	11.2	11.45	17.07
3	3.5	88.9	0.216	5.5	7.58	11.31
	3.5	88.9	0.254	6.5	8.81	13.21
	3.5	88.9	0.289	7.3	9.92	14.69
	3.5	88.9	0.375	9.5	12.53	18.6
	3.5	88.9	0.43	10.9	14.11	20.97
	3.5	88.9	0.476	12.1	15.39	22.92
	3.5	88.9	0.53	13.5	16.83	25.1

Size	Outside Diameter		Wall Thickness		Weight	
	in	mm	in	mm	lb/ft	kg/m
3 1/2	4	101.6	0.226	5.7	9.12	13.48
	4	101.6	0.262	6.7	10.47	15.68
	4	101.6	0.33	8.4	12.95	19.31
	4	101.6	0.415	10.5	15.9	23.59
	4	101.6	0.5	12.7	18.71	27.84
	4	101.6	0.61	15.5	22.11	32.91
4	4.5	114.3	0.271	6.9	12.25	18.27
	4.5	114.3	0.337	8.6	15	22.42
	4.5	114.3	0.38	9.7	16.77	25.02
	4.5	114.3	0.43	10.9	18.71	27.79
	4.5	114.3	0.5	12.7	21.38	31.82
	4.5	114.3	0.56	14.2	23.59	35.05
	4.5	114.3	0.63	16	26.06	38.79
	4.5	114.3	0.63	16	26.06	38.79

*Other grades or sizes may be available upon request.

EWR PIPES

Size Range / Casing

Size	Outside Diameter		Wall Thickness		Weight	
	in	mm	in	mm	lb/ft	kg/m
4	4.5	114.3	0.205	5.2	9.41	13.99
	4.5	114.3	0.224	5.7	10.24	15.27
	4.5	114.3	0.25	6.4	11.36	17.03
	4.5	114.3	0.29	7.4	13.05	19.51
	4.5	114.3	0.337	8.6	15	22.42
6	6.625	168.3	0.288	7.3	19.51	28.98
	6.625	168.3	0.352	8.9	23.6	34.98
	6.625	168.3	0.417	10.6	27.67	41.22
	6.625	168.3	0.475	12.1	31.23	46.61
8	8.625	219.1	0.264	6.7	23.6	35.09
	8.625	219.1	0.304	7.7	27.04	40.14
	8.625	219.1	0.352	8.9	31.13	46.13
	8.625	219.1	0.4	10.2	35.17	52.55
	8.625	219.1	0.45	11.4	39.33	58.39
	8.625	219.1	0.5	12.7	43.43	64.64
	8.625	219.1	0.557	14.1	48.04	71.28
10	10.75	273.1	0.279	7.1	31.23	46.57
	10.75	273.1	0.35	8.9	38.91	57.99
	10.75	273.1	0.4	10.2	44.26	66.13
	10.75	273.1	0.45	11.4	49.55	73.57
	10.75	273.1	0.495	12.6	54.26	80.94
	10.75	273.1	0.545	13.8	59.45	88.24
	10.75	273.1	0.595	15.1	64.59	96.07
	10.75	273.1	0.672	17.1	72.4	107.95
	10.75	273.1	0.734	18.6	78.59	116.73
	10.75	273.1	0.797	20.2	84.8	125.98

Size	Outside Diameter		Wall Thickness		Weight	
	in	mm	in	mm	lb/ft	kg/m
16	16	406.4	0.375	9.5	62.64	92.98
	16	406.4	0.438	11.1	72.86	108.2
	16	406.4	0.495	12.6	82.05	122.36
	16	406.4	0.656	16.7	107.6	160.49
20	20	508	0.438	11.1	91.59	136.01
	20	508	0.5	12.7	104.23	155.12
	20	508	0.635	16.1	131.45	195.3

*Other grades or sizes may be available upon request.